



Suspended load modelling in revitalization projects
Case study on the Alpine Rhine River

David Vetsch, Benjamin Hohermuth, Andris Wyss, Florian Hinkelammert 7th BASEMENT Users Meeting February 3, 2022, online via Zoom





Project team

Work:

Benjamin Hohermuth, Andris Wyss

Lead:

David Vetsch, Florian Hinkelammert

Advisors:

Daniel Conde, Francesco Caponi

Project commissioned by:
 IRR – International
 company for the regulation
 of the Alpine Rhine



Contents

- Overview
- Objectives
- Software & Models
- Processes
- Results
- Conclusions

Mittelgerinnewuhr 80.2 – 82.4 L, 24.06.2016

Foto Nr.: 5574



Foto Nr.: 5575



Foto Nr.: 5576





Foto Nr.: 5577



Overview


- Alpine Rhine
- HQ100
 2'600 m³/s
- Total annual sediment load ca. 2.5x10⁶ m³/a






Overview

around 1860



today






Objectives


Planned restoration measures

- Widening of regulated channel
- Lowering of flood plain
- -> less flood plain area, more frequent flooding

Main questions

- ? Deposition of fine sediments on flood plains
- ? Impact on channel conveyance
- ? Effect of vegetation





Software & Models


Software:

BASEMENT v3.1.x (development version)

- Models:
 - *k*-ε turbulence model:
 - transversal momentum exchange
 - turbulent diffusion (local dispersion) for advection-diffusion equation
 - Shear stress splitting:
 bed shear stress ↔ flow resistance
 - local erosion and deposition
 - effect of vegetation




- Suspended sedimentand bed load transport model:
 - susp. sed. load:van Rjin (erosion), Xu (deposition)
 - bed load: Wong & Parker
 - fixed bathymetry from laboratory experiments
 - uniform sediment
- BASEveg: conceptual (flow resistance), not dynamic






Processes

distinct shear zones (current situation)



relevant parameters (project situation)






Setup

mesh and roughness

	Bestand	Projektzustand	
Abschnitt	km 78.0 - 86.4	km 79.6 - 86.4	
Anzahl Elemente	775'000	445'000	
Anzahl Knoten	390'000	225'000	

upstream boundary, 2016 flood




	Bestand		Projektzustand	
	A _{max} [m ²]	<i>k</i> _s [m]	A_{max} [m ²]	<i>k</i> _s [m]
Gerinnesohle	10	0.1	10	0.1
Gerinneböschung Fuss	1	1.0	-	-
Vorgrund	1	0.6	-	-
Gerinneböschung	1	0.6	2	0.6
Vorland	10	0.1	10	0.1
Dammböschung	2	0.36	5	0.36
Bewuchs «wenig»	-	0.1	-	0.1
Bewuchs «mittel»	-	0.25	-	0.25
Bewuchs «viel»	-	1	-	1

Results

Calibration / validation / model sensitivity

- based on current situation
- 2016 flood
- qualitative assessment (pictures, experts)
- sensitivity of different parameters (grain size, angle of repose, local dispersion)
- relevant: different grain size










© VAW





Results

Sedimentation (project)

- 2016 flood
- d = 100 µm
- distinct increase of sediment deposition
- flood plain: 0.05 0.8 m
- groyne fields: up to 3 m
- gravel bars: 0.2 2 m








© VAW





Results

Effect of vegetation (project)

- 2016 flood
- little effect on deposition
- flood plains: more pronounced dep. smaller area
- gravel bars:+0.2 bis 0.5 m







© VAW





Conclusions

- distinct increase of sediment deposition
- no clear remobilization during successive floods (HQ₂ to ~HQ₂₀)
- vegetation mainly affects distribution of sediments but only slightly affects total volume
- quantitative assessment is mainly limited by data for model calibration
- turbulence model allows for realistic simulation of shear zones
- the more complex the model,
 - the more detailed the required data basis
 - the more computationally expensive the simulation





Outlook

- peer reviewed journal papers
 - turbulence model
 - suspended sediment transport model
- reports / engineering journal contribution
 - BAFU Umwelt Wissen (report in English, German, French, Italian)
 - WEL (Swiss journal)

- tutorials (expected)
 - turbulence modelling
 - suspended sediment transport
 - vegetation